

77% ROAD GRADE SOLID CALCIUM CHLORIDE

Product Data Sheet

General Description

Road grade calcium chloride (CaCl_2) is produced to suit the specific needs of our road maintenance and deicing customers. Our ISO system ensures that our high standards of production are maintained and improved.

Applications

TETRA Road grade calcium chloride is used mainly for maintenance of gravel and dirt roads and in deicing applications on paved and unpaved surfaces.

Calcium chloride is both hygroscopic and deliquescent. These related properties both involve absorption of atmospheric moisture and retention of moisture present in the soil, making it ideal for dust binding on gravel and dirt roads. Unpaved surfaces treated with this product, when cured and compacted, form a hard and smooth riding surface, significantly reducing dust displacement.

Calcium chloride is a very effective deicing agent. calcium chloride is effective to temperatures as low as -30°C . The use of calcium chloride to melt snow and ice and to prevent low friction conditions is an efficient tool in any winter road maintenance program.

Availability

Solid road grade calcium chloride flakes are produced in Finland. Solid road grade calcium chloride is available worldwide through our network of distributors in the following packaging options.

SOLID ROAD GRADE CaCl_2 PACKAGING

Package	Dimensions LxWxH	Units
25 kg Bag	1100x900x1150	40/Pallet
1000 kg Big Bag	1000x1000x1350	1
Bulk	N/A	N/A

TETRA Chemicals Europe

Sweden

Box 901, SE-251 09
Helsingborg, Sweden
Phone: +46 42 453 27 00
Fax: +46 42 453 27 80

Finland

Box 551, FI-67701
Kokkola, Finland
Phone: +358 6 8282 111
Fax: +358 6 8282 575

www.tetrachemicals.com

Safety and Handling

Calcium chloride is a strong salt. Protective clothing, rubber gloves and eye protection are recommended. Rubber safety boots should also be worn in work areas, since calcium chloride can damage leather. This product should be handled in areas with proper ventilation. Before using this product, refer to the MSDS (available on the Company's website) for complete safety and handling guidelines. For proper disposal guidelines for calcium chloride wastes, consult the appropriate local regulatory authorities.

PHYSICAL PROPERTIES

Appearance	White flakes
Odor	None
Bulk Density	820 kg/m^3

CHEMICAL PROPERTIES

	Specification	Typical Value
CaCl_2 Concentration	> 77%	77%
pH (in 10% CaCl_2 solution @ 20°C)	9 - 11	10.3

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's work-place and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.